

SIDEWALK

SIDEWALK

SIDEWALK

SIDEWALK



100'
100'

* "No parking" signs must be placed a MINIMUM of 24 Hours in advance.

*No parking signs wording must match either #1 or #2 below:

#1 = 24 hours: "No parking anytime TOW AWAY ZONE at all times"

#2 = Limited: "No parking anytime TOW AWAY ZONE 7am TO 5pm"

*No parking sign spacing is approximately 20 - 25 feet apart.

*Contractor must resolve all local access and safety issues.

*All barricades, cones, and signs must be in accordance with the latest edition of the Manual on Uniform Traffic Control Devices (MUTCD).

*Flaggers must follow MUTCD guidelines. Flaggers must be certified and use and wear safety equipment as required.

SIDEWALK

SIDEWALK

Minimum 12 ft. Travel Lane must be maintained at all times.

Work Area

SIDEWALK

Cone Spacing: 25 ft. apart

Taper - 50-100 feet max

Sign Spacing to be approx. 100 feet min. apart for low-speed local streets (<35mph).

100'
100'



SIDEWALK



Indicate North On Plan

Do not block or encumber sidewalks at any time

Drawing Not to Scale



City and County of Denver
Department of Transportation
& Infrastructure

Street - Two Flagger Closure

Residential Roads Only

Revised 9/28/2022